

A3		FIRST ANGLE		LENGTH/ DIAMETER		0.5-6	>6-30	>30-120	>120-400	>400-1000	>1000-2000	>2000-4000	RADIUS/ CHAMFER		0.5-3	>3-6	>6	ANGLE (shorter side length)		0-10	>10-50	>50-120	>120-400	>400	TOLERANCE		± 1°	± 0.5°	± 0.3°	± 0.15°	± 0.1°		
				TOLERANCE		± 0.1	± 0.2	± 0.3	± 0.5	± 0.8	± 1.2	± 2			TOLERANCE		± 0.2	± 0.5	± 1														

Z = LEG LENGTH
ANSI/AWS A2.4-98
WELDING SYMBOLS ARE
USED IN THIS DRAWING.
REFER TO DRAWING
AAABADJ FOR CONVERSION
TO ISO SYMBOLS.

WELDS

OTHER SIDEARROW SIDE

2024-07-24

其余

技术说明:

1、本件适用 $\leq 2.5\text{m/s}$, 允许质量 $(P+Q) = 1000 \sim 4500\text{kg}$,
(最终以有效期内的型式试验证书为准), 在此范围内具体见订单参数;

2、本件可匹配导轨工作面宽度为15.88mm、16mm,
在此范围内具体见订单参数;

3、导向面润滑状况为: 润滑;

4、本图所示为1组, 每台电梯配2组;

5、依据GB/T 7588.2-2020中5.3.4 a) 所应用的质量可以与允许质量相差 $\pm 7.5\%$

件号	额定速度 m/s	允许质量 (P+Q)Kg	导轨面工作宽度B	型号	提拉方式	品牌
VKS3H059001	V=1.0	2350	10mm	OX-188	双楔块 双提拉	沃克斯 迅达
VKS3H059002		3150	15.88mm			
VKS3H059003		3700				
VKS3H059004	V=1.5	2350				
VKS3H059005		3150				
VKS3H059006		3700				
VKS3H059007	V=1.0	2350	10mm			
VKS3H059C01	V=1.0	见订单	15.88mm			
VKS3H059C02	V=1.0	见订单	15.88mm			
VKS3H059C03	V=1.5	见订单	15.88mm			

AX188V025

						Volkslift Schindler	渐进式安全钳	VKS3H059		
△	增加C01--C03件号;	2024.7.3	徐星涛	王勇新	24701	绘图 DRAWN 王勇新	材料: 组装件	首次下发版本 FIRST VERSION	重量 WEIGHT	比例 PROPORTION
	整版换页, 调整渐进式安全钳P+Q的质量, 增加技术要求。	2024.5.30	徐星涛	王勇新	24501	校对 CHK 李洋		22201		1:3
						批准 APPD 闵传宏		SHEETS 2	1	SHEET
标记 MARK	更改原因及说明 CHANGE REASONS AND INSTRUCTIONS	更改日期 CHANGE DATE	更改 CHANGE	审查 CHECK	版本 VERSION	日期 DATE	MATERIAL:	2022.02.20		

A3

FIRST ANGLE

LENGTH/
DIAMETER
TOLERANCE

0.5-6
 ± 0.1

>6-30
 ± 0.2

>30-120
 ± 0.3

>120-400
 ± 0.5

>400-1000
 ± 0.8

>1000-2000
 ± 1.2

>2000-4000
 ± 2

RADIUS/
CHAMFER
TOLERANCE

0.5-3
 ± 0.2

>3-6
 ± 0.5

>6
 ± 1

ANGLE (shorter side length)
TOLERANCE

0-10
 $\pm 1^{\circ}$

>10-50
 $\pm 0.5^{\circ}$

>50-120
 $\pm 0.3^{\circ}$

>120-400
 $\pm 0.15^{\circ}$

>400
 $\pm 0.1^{\circ}$

Z = LEG LENGTH
ANSI/AWS A5.4-98
WELDING SYMBOLS ARE
USED IN THIS DRAWING.
REFER TO DRAWING
AAAGBAUJ FOR CONVERSION
TO ISO SYMBOLS.

OTHER SIDE ARROW SIDE

WELDS

2026-04-17

其余

The technical drawing illustrates the VKS3H059 safety bracket assembly from three perspectives:

- Front View (Top Left):** Shows the main body with a height dimension of (195) and a base width of (B+36). It features four vertical support columns and a central mounting point.
- Side View (Top Right):** Shows the profile of the bracket with a height of 10 and a base width of 16. A callout indicates a standard M10 bolt at position (17).
- Top View (Bottom Left):** Provides a plan view with overall dimensions of 225x205mm. It shows four mounting holes labeled 4-Ø18 and four additional holes labeled 4-M16. Vertical spacing between hole rows is 70mm and 65mm. Horizontal spacing includes 110mm between inner holes and 205mm between outer holes. The bottom edge has a total width of 165mm, subdivided into (28), 38, and 70mm segments. Mounting feet are shown with a width of 3±0.5mm. The guide rail face width is denoted as B.

技术说明:

- 1、本件适用 $\leq 2.5\text{m/s}$, 允许质量(P+Q)=1000~4500kg,
(最终以有效期内的型式试验证书为准), 在此范围内具体见订
单参数;
- 2、本件可匹配导轨工作面宽度为15.88mm、16mm,
在此范围内具体见订单参数;
- 3、导向面润滑状况为: 润滑;
- 4、本图所示为1组, 每台电梯配2组;
- 5、依据GB/T7588.2-2020中5.3.4 a) 所应用的质量可以与允许质量
相差 $\pm 7.5\%$

件号	额定速度 m/s	允许质量 (P+Q)Kg	导轨面工作宽度B	型号	提拉方式	品牌			
VKS3H059I01	V=0.5	2350	10mm	OX-188	双楔块 双提拉	沃克斯 迅达			
VKS3H059I02		3150	15.88mm						
VKS3H059I03		3700							
VKS3H059C11		见订单	10mm						
VKS3H059C12		见订单	15.88mm						
VKS3H059C13	V=1.0	见订单	16mm						
VKS3H059C14		见订单	10mm						
VKS3H059C15		见订单	15.88mm						
VKS3H059C16		见订单	16mm						

						Volkslift Schindler		渐进式安全钳		VKS3H059									
						绘图 DRAWN 王勇新 校对 CHK 李洋 批准 APPD 闵传宏	材料: 组装件		首次下发版本 FIRST VERSION	重量 WEIGHT	比例 PROPORTION								
标记 MARK	更改原因及说明 CHANGE REASONS AND INSTRUCTIONS					更改日期 CHANGE DATE	更改 CHANGE	审查 CHECK	版本 VERSION	日期 DATE	2022.02.20	SHEETS 2	2 SHEET						