

基本尺寸	0~6	6~30	30~120	120~400	400~1000	1000~2000	2000~4000
公差	0.1	0.2	0.3	0.5	0.8	1.2	2.0

Technical drawing of the DBG-340 mechanical device, showing a side view with dimensions and a top view. The side view includes dimensions: 12°, 0.6, 14, (230), 325, 35, 40, 60, 2-∅11, 45, 45, 4-5×20, 50, 15, (150), and 12°. The top view shows a long central shaft with a label "DBG-340 (具体按实际可作调整, DBG ≥ 1100mm)".

可动面距 DDO (DDO > 1100mm)

Technical drawing of a mechanical assembly, likely a valve or actuator, showing a side view with dimensions and labels. The drawing includes a central horizontal shaft with a spring mechanism on the left and a handle on the right. Dimensions are given in millimeters. Labels include 1, 3, 4, 5, 6, 7, 8, 11, 12, 13, 15, 17, 20, 21, 240, 208, 121, 348, 220, and 170. A note at the top right specifies "可动面距 DDO (DDO > 1100mm)".

								5	OX188BT. 2	长拉杆组件	1		1.64	1.64	
								4	OX-188T. 1. 1-2	轴衬套	4	工程塑料	0.01	0.04	
15	GB/T 91-2000	开口销3. 2X25	4		1.74	6.96		3	OX188BT. 1	联动组件	2		1.47	2.94	
14	OX188T. 5	钢丝绳连接件	1		0.03	0.03		1	OX188BT. 4	提拉手焊件	2		0.41	0.82	
13	OX188BT-4	拉手杆	1	Q235A/8. 0	0.44	0.44		序号	代 号	名 称	数量	材料说明	重量	总重	备注
12	GB/T 93-1987	弹性垫圈10	2		2.16	4.32									
11	GB/T 5783-2000	螺栓M10×20	2		23.05	46.1									
10	UKS	行程开关	1		0.09	0.09	外购件								
9		开关支架	1	Q235A/2. 0	0.11	0.11		标记	处数	分 区	文件更改号	签 名	年、月、日		
8	GB/T 6170-2000	螺母M12	2		16.52	33.04		设计			标准化				
7		左右旋螺母	1		0.12	0.12		校 对							
6	OX188BT. 3	短拉杆组件	1		0.50	0.5		审 核							
序号	代 号	名 称	数量	材料说明	重量	总重	备注	工 艺			批 准			共 1 张	第 1 张
													宁波奥德普电梯部件有限公司		
													单提拉联动机构		
													OX-188BT		