



- | 件号 | V(m/s) | 适用(P+Q)范围(kg) | 导轨宽度(mm) | 高度H | 型号 |
|--------------|--------|---------------------------|----------|-----|---------|
| YSFS3H505001 | 1 | $900 \leq P+Q \leq 2800$ | 10 | 150 | OX-188B |
| YSFS3H505002 | 1.5 | $900 \leq P+Q \leq 2800$ | 10 | 150 | OX-188B |
| YSFS3H505003 | 1.75 | $900 \leq P+Q \leq 2800$ | 10 | 150 | OX-188B |
| YSFS3H505004 | 1 | $900 \leq P+Q \leq 2800$ | 15.88 | 150 | OX-188B |
| YSFS3H505005 | 1.5 | $900 \leq P+Q \leq 2800$ | 15.88 | 150 | OX-188B |
| YSFS3H505006 | 1.75 | $900 \leq P+Q \leq 2800$ | 15.88 | 150 | OX-188B |
| YSFS3H505007 | 1 | $1000 \leq P+Q \leq 4000$ | 15.88 | 195 | OX-188 |
| YSFS3H505008 | 1.5 | $1000 \leq P+Q \leq 4000$ | 15.88 | 195 | OX-188 |
| YSFS3H505009 | 1.75 | $1000 \leq P+Q \leq 4000$ | 15.88 | 195 | OX-188 |
| YSFS3H505010 | 1 | $900 \leq P+Q \leq 2800$ | 16 | 150 | OX-188B |
| YSFS3H505011 | 1.5 | $900 \leq P+Q \leq 2800$ | 16 | 150 | OX-188B |
| YSFS3H505012 | 1.75 | $900 \leq P+Q \leq 2800$ | 16 | 150 | OX-188B |
| YSFS3H505013 | 1 | $1000 \leq P+Q \leq 4000$ | 16 | 195 | OX-188 |
| YSFS3H505014 | 1.5 | $1000 \leq P+Q \leq 4000$ | 16 | 195 | OX-188 |
| YSFS3H505015 | 1.75 | $1000 \leq P+Q \leq 4000$ | 16 | 195 | OX-188 |
| YSFS3H505999 | 赋值 | 赋值 | 赋值 | 赋值 | 赋值 |

						宁波奥德普							
										安全钳			
标记	处数	分区	更改文件号	签名	年月日								
设计			标准化			阶段标记		重量	比例	YSFS3H505			
校对						-	-	-	-			0kg	1:3
审核						共 1 张 第 1 张							
工艺			批准										